



C/Barrio la Mina s/n Nave 2
39792-Gajano (Cantabria)
Teléfono: (34) 942 502 334 Fax: (34) 942 502 044
Móvil: (34) 682 348 548
E-mail: ekyma@ekyma.es - www.ekyma.es
ESPAÑA

TECHNICAL RECORD EKYNET-100-PLUS

DESCRIPTION:

EKYNET-100- PLUS Cleaning booster for soils difficult to remove such as charcoal, graphite, burned oils, remains of lacquers, paints, etc. and is exclusively developed for use in ultrasonic equipment.

EKYNET-100- PLUS is a red liquid emulsifiable in water.

EKYNET-100-PLUS contains in its formula, surfactants which reduce the resistance of the surface, giving it a great cleaning power.

EKYNET-100-PLUS is particularly suitable for hot degreasing ultrasonic equipment automotive companies and industry in general.

PHYSICAL AND CHEMICAL PROPERTIES:

Color: Red

Odor: Characteristic

Density: 0,920-1,020 g/ml

METHODS AND INSTRUCTIONS FOR USE:

Dosage: 0,50% to 1,5% in water.

Temperature: 50°C to 75°C.

Time: 30 to 60 minutes

MODE OF SUPPLY:

Bottle of 2 liters.

Jerrycan of 220 liters.

Container of 1000 liters.