



C/Barrio la Mina s/n Nave 2
39792-Gajano (Cantabria)
Teléfono: (34) 942 502 334 Fax: (34) 942 502 044
Móvil: (34) 682 348 548
E-mail: ekyma@ekyma.es - www.ekyma.es
ESPAÑA

TECHNICAL RECORD EKYNET - 120

DESCRIPTION:

EKYNET- 120 is a degreaser specially developed for hot degreasing in ultrasonic equipment of **ferrous** parts as well as **aluminum** parts and light alloys.

EKYNET- 120 contains in its formulation sequestrants that prevent the precipitation of calcium and magnesium salts, when used with hard water without altering its cleaning power. Its surfactants, carefully selected, facilitate penetration of the product into the soil, giving it a great detergent and degreasing power; it contains in its formulation, moisturizers that reduce the tension of the surface, giving it a high degreasing power. Does not contain NTA, cationic surfactants and nonylphenol ethoxylates.

APPLICATIONFIELDS:

EKYNET- 120 It is particularly suitable for hot degreasing in ultrasound equipment, both in automotive companies as well in the industry in general.

PHYSICAL AND CHEMICAL PROPERTIES:

Color: Blue

Odor: Characteristic

pH: 11-12

METHODS AND INSTRUCTIONS FOR USE:

Dosage: 3 to 5% in water.

Temperature: 50°C to 75°C.

Time: 30 a 60 minutes.

Cleaning and descaling char: we recommend adding our booster **EKYNET-120-PLUS** for more surfactant power.

MODE OF SUPPLY:

Bottle of 25 liters.

Jerrycan of 220 liters.

Container of 1200 liters.