



C/Barrio la Mina s/n Nave 2  
39792-Gajano (Cantabria)  
Teléfono: (+34) 942 502 334 Fax: (+34) 942 502 044  
Móvil: (+34) 682 348 548  
E-mail: [ekyma@ekyma.es](mailto:ekyma@ekyma.es) - [www.ekyma.es](http://www.ekyma.es)

## FICHA TÉCNICA EKYNET-185

### DESCRIPTION:

It is a white solid product soluble in water, consisting a mixture of sequestrants, surfactants and caustic alkali.

Aqueous solutions of EKYNET-185, are effective in removing oxide of all types of steel.

It forms water-soluble complexes with iron salts and other metals, leaving the surfaces clean and bright.

Is as effective as the acid stripping products, but it has none of its disadvantages and, in general, the tendency to further oxidation is less.

Removes grease rapidly and char and some air-dried paints.

### PHYSICAL AND CHEMICAL PROPERTIES:

Appearance: white granular powder

Free Alkalinity: 40% as Na<sub>2</sub>O.

### METHODS AND INSTRUCTIONS FOR USE:

EKYNET-185 is used as an aqueous solution with a concentration of 5 to 10% in water.

Temperature: 60 ° C and 80 ° C.

EKYNET-185 attacks aluminum.

It does not attack PTFE. EKYNET-185 has a slight effect on magnesium, cadmium, nickel, cobalt, titanium and copper.

It does not attack polyethylene, PVC and PTFE.

### MODE OF SUPPLY:

Bag of 25 kilos

Pallet of 1000 kilos